



GOVERNMENT POLYTECHNIC, WASHIM

Risod Road, Lakhada, Washim

Dist- Washim (M.S.) Pin. 444505

Phone No. (Off) 07252-232252

E-mail:- office.gpwashim@dtmaharashtra.gov.in

Principal- 07252- 232085

Website- www.gpwashim.edu.in



No. GPW/CS/Quotation/2018/ 3458

DATE: 05/11/2018

QUOTATION AUTOMOBILE ENGG. DEPT.

To,

M/s.

As list attached

Subject :- Quotation for the supply of Automobile Engg. Department Equipment's/Machines

R/Sir,

You are requested to send your most comparative rate for the supply of following items.

Last Date: 26/11/2018 (5.30 pm)

Open Date : 27/11/2018


At : 11.00 am

CONDITIONS

1. Rate required should be clearly mentioned with delivery and installation at the institution, inclusive of all taxes or otherwise.
2. Detailed specifications of the articles you intend to supply should be given if not according to specifications laid down here under. The quotation must be supported by necessary technical literature/specification etc
3. GST/PAN etc should be shown extra. If applicable.
4. The material should be supplied and installed within 20 days from the date of order/list of materials attached shown below.
5. Warranty for each item should be clearly specified. Minimum 12 months warranty from date of billing/installation.
6. The earliest delivery period should be quoted, if you cannot supply within the period mentioned above.
7. Quotation should be in sealed covers super scribed with "Quotation for the supply of Automobile Engg. Department Equipment's/Machines" Due on 26/11/2018 in two separate envelopes 1) Technical 2) Financial
 - i. Technical sealed envelope should contain Authorized dealer certificate /GST/PAN/CST If applicable
 - ii. Financial sealed envelope should contain specification and rate.
8. Quotation should be valid for 03 months from the date of your quotation letter.
9. Quotation not complying with the above conditions and incomplete ones will not be considered.
10. Conditions of advance payment or payment against dispatch documents will not be considered.
11. Supplier must not be a defaulter to any Government authorities and must not have blacklisted/ debarred from supplying goods.
12. The quotation must comply with all technical requirements of the user department, mere quoting of lowest price will not be the criteria for award.
13. This office reserve the right to reject any or all quotations, without assigning any reason (s) and to call for any other details or information from any of tenders.

Sr. No	Name of the Item	Specification	Approx. Expect. Cost	Quantity Required
1	Environment meter multifunctional 5 in 1	Meter with light (LUX), sound, humidity, temperature & wind speed measurement capability & digital display. Make- Exttech or equivalent reputed manufacturer	15,000	01
2	Timing light (Neon) stroboscope	Inductive type of clamp, self-powered, neon timing light with all accessories	2,000	01
3	AC Gas leak detector	sensor with high sensitivity, 3g/yr (0.1oz/yr), detect All KINDS OF halogenated refrigerant, 14 inches (35.5cm) flexible stainless steel probe can reach to almost any tight space, Single color LED display with 6-level leak alarm, tricolor display of battery voltage, Real time sensitivity and RESET time sensitivity adjustment, One extra spare sensing tip should be included.	4,000	01
4	Growler Armature Tester with meter	Growler Armature Tester with meter with accessories	3,000	01
5	Turbocharger cut sectional view	cut sectional demonstration model with all component with good view with paint & mounted on solid base	4,000	01
6	Head light aligner	Head light Aligner with ISO color technology, Rotational mast, Durable and lightweight, Adjustable height, Laser floor slope	16,000	01
7	Belt Tension Gauge	Scale reads 30-180 inch pounds, handy universal belt tension gauge and the OTC family of belt tensioning tools, with all accessories	8,000	01
8	Battery Charger	<ul style="list-style-type: none"> Powerful electronic charger for 12V & 24V Lead Acid standard, maintenance free & greatly discharged batteries. Effective & battery-protecting charging through temperature compensation. Adaptable charging current due to infinitely variable charging current adjustment. Suitable for trickle charging & floating mode operation. Charges the batteries both when installed in the vehicle and when in the dismantled condition. Display of operating state, charge state, incorrect polarity & malfunction. Protection of electrical components (such as airbags & engine control units) against damage during charging. Protection against overcharging, reverse polarity. Make- Bosch or equivalent reputed manufacturer	20,000	01
9	Automotive Multimeter with kit	Automotive digital multimeter with ohms, current, voltage, capacitance measurement, capable of temperature, pressure, diode testing, frequency duty cycle, RPM with all testing probes accessories manual & auto ranging function milisec pulse width measurement for fuel injector safety cat III and cat IV Make- Fluke or equivalent reputed manufacturer	50,000	01

10	Auto Measurement tools & Equipment	<ul style="list-style-type: none"> • telescopic bore gauge set of 6 (8-12.7 mm, 12.7-19 mm, 19-32 mm, 32-54 mm, 54-90 mm, 90-150 mm), -1 set; • wire gauge-1 no; • feeler gauge 4cm- 1no; • filler gauge 12 cm- 1 no; • screw pitch gauge-1 no; • straight edge 24" (Precision ground to + .001")- 1 no; • bevel edge/protractor- 1 no; • Dial Vernier Caliper 0-30cm (Checks OD, ID, step and depth with 0.02 mm Least Count) – 1 no ; • 25mm Digital External Micrometer- 1 no; • micrometer inside 25/30mm, 1 no; • sine bar 5"- 1 no; • 32 Pcs. Slip Gauge Set – 1 set; • dial gauge with magnetic dial gauge stand (adaptive holding fixture)- 1 set; • set of radius gauge; • go/ no go 0-25 mm gauge- 1 no; • spark plug gap gauge – 1 no; 	53,000	01 set
11	V block set (Magnetic)	size of 2-3/4"x3-3/4"x4" ideal for holding round and irregular shapes for scribing, grinding, measuring and matching. It comes in fine precision ground finish and with lever operated on/off switch.	6,000	02
12	Injector Cleaning & tester Unit	for six-cylinder car, Block 2 tube for 4 jar, machine must fit for most of petrol injector(come with lots of adapters), must supports most Indian car models.	55,000	01
13	Two Post Electrohydraulic Lift	capacity 3.5 ton, comes with basic plate, lifting height-1800mm, rise <50 sec, drop time > 20 sec, motor power 2.2 kw, three phase , double cylinder fall proof safety rack with foundation & installation	1,20,000	01
14	Wheel Balancing Machine	Vieographic wheel balancing machine with 19" TFT Monitor & Protection cover, Max wheel weight 65 kg, Max Tier Diameter 47" Rim Dia 10"- 24", Width 5"- 14" with foundation & installation	1,25,000	01


(Dr. V. R. Mankar)
Principal
Govt. Polytechnic, Washim.

Copy To

- 1) Main Notice Board for Display
- 2) Portal Manager for display on web site.